

Isosound

Ondervloer voor parket/laminaat en PVC

Sous-couche pour parquet/ sol stratifié et PVC

Voor PVC / Pour PVC

Alulaag naar onderen leggen.

Poser la face aluminium vers le bas.



1 ●●●●●
Beschermt de vloer/Protection du sol

2 ●●●●●
Verbetering comfort/Amélioration du confort

3 Eenvoudig te leggen
Pose facile

4 Toepassing: extra geluidsisolatie, vloerverwarming/koeling
Application: Isolation phonique supplémentaire, chauffage/refroidissement par le sol

Technical Data:

Punctual Conformability (PC)	up to 1 mm
Compressive Strength (CS)	ca. 298 kPa
Compressive Creep (CC)	> 50 kPa
Resistance to large ball (RLB)	800 mm
Water vapour diffusion resistance (SD > 75m)	Yes
Thermal Resistance (R)	ca. 0,008 m ² K/W
Impact Sound Reduction (IS/ΔL _w)	up to 18 dB
Weight ca.	20 kg
Fulfils all minimum requirements of the EPLF	Yes

Uitleg / explication / Erklärung / explanation



= minimumeis vloerenproducenten = minimum Anforderung
= au minimum fabricants de planchers = minimum requirement

Uitleg / explication / Erklärung / explanation



= beste keus = beste Wahl
= meilleur choix = best choice

NL • Afmeting: 1 x 10 = 10m²
• Geschikt voor vloerverwarming ✓
• Geschikt voor vloerkoeling ✓

D • Format: 1 x 10 = 10m²
1 Schützt den Fußboden
2 Erhöht den Wohnkomfort
3 Einfach zu verarbeiten
4 Anwendung: zusätzlich Trittschallminderung / Fußbodenheizung und -kühlung
• Eignung bei Fußbodenheizung ✓
• Eignung bei Fußbodenkühlung ✓


FR • Dimension: 1 x 10 = 10m²
• Convient pour le chauffage par le sol ✓
• Convient pour le refroidissement par le sol ✓

UK • Dimension: 1 x 10 = 10m²
1 Protects the floor
2 Improves living comfort
3 Simple to process
4 Application: extra sound insulation / underfloor heating & cooling
• Compatibility with underfloor heating ✓
• Compatibility with underfloor cooling ✓

0621-5155



Isosound
Ca. 2 mm
10 m²



maclean
HOME OF IDEAS
Mac Lean Products B.V. - Industrieterrein Moerdijk
Logistic Boulevard 3, 4791 VC Klundert, The Netherlands
www.macleanproducts.nl - info@macleanproducts.nl