

Isosound

Ondervloer voor parket/laminaat

Sous-couche pour parquet et sol stratifié



1



Beschermt de vloer/Protection du sol

2



Verbetering comfort/Amélioration du confort

3

Eenvoudig te leggen
Pose facile

4

Toepassing: extra geluidsisolatie, vloerverwarming/koeling
Application: Isolation phonique supplémentaire, chauffage/refroidissement par le sol



Technical Data:

Punctual Conformability (PC)	up to 1 mm
Compressive Strength (CS)	ca. 298 kPa
Compressive Creep (CC)	> 5 kPa
Resistance to large ball (RLB)	> 100 cm
Water vapour diffusion resistance (SD > 75)	Yes
Thermal Resistance (R)	ca. 0,008 m ² K/W
Impact Sound Reduction (IS/ ΔL_w)	up to 20 dB
Weight ca.	20 kg
Fulfils all minimum requirements of the EPLF	Yes

Uitleg / explication / Erklärung / explanation



= minimumeis vloerenproducenten = minimum Anforderung
= au minimum fabricants de planchers = minimum requirement

Uitleg / explication / Erklärung / explanation



= beste keus = beste Wahl
= meilleur choix = best choice

NL

- Afmeting: 1 x 10 = 10 m²
- Geschikt voor vloerverwarming ✓
- Geschikt voor vloerkoeling ✓

D

- Format: 1 x 10 = 10 m²
- 1 Schützt den Fußboden
- 2 Erhöht den Wohnkomfort
- 3 Einfach zu verarbeiten
- 4 Anwendung: zusätzlich Trittschallminderung / Fußbodenheizung und -kühlung
- Eignung bei Fußbodenheizung ✓
- Eignung bei Fußbodenkühlung ✓

FR

- Dimension: 1 x 10 = 10 m²
- Convient pour le chauffage par le sol ✓
- Convient pour le refroidissement par le sol ✓

UK

- Dimension: 1 x 10 = 10 m²
- 1 Protects the floor
- 2 Improves living comfort
- 3 Simple to process
- 4 Application: extra sound insulation / underfloor heating & cooling
- Compatibility with underfloor heating ✓
- Compatibility with underfloor cooling ✓

1216-5155



Isosound
Ca. 2 mm
10 m²

Postbus 6078
4780 LX Moerdijk

